

Experimental Investigation of the Wave Run Up on a TLP Floating Wind Turbine

Marinos P. Charalambous^{1, 2}

Email: marinoscharalambous93@gmail.com

Co- Author: Professor Dr. Eng. Thomas P. Mazarakos¹

¹Naval Architecture Department, University of West Attica, Athens, Greece


²One Tech Services LTD




Contents

- Introduction
- Construction of the model
- Experimental campaign
- Results
- Conclusions
- Acknowledgments

Introduction




Turbine blades in
stationary condition




Turbine blades in
operating condition


Introduction




Important for the
Environmental



Abundant
Availability
of wind




Tanks & Ballast
used in the
Offshore oil &
Gas Industry



Depleting
Hydrocarbon
Resources

Main characteristics of the model

- The central vertical cylinders.
- The cross braces.
- The base of the wind turbine tower.
- The anchor base at the bottom.
- The Vertical tower.
- The Wind Turbine (WT) engine.
- The blades of the wind turbine.



Weight Pre-Calculation

Element		Length [mm]	Quantity	Outside Diameter [mm]	Inside diameter [mm]	Thickness [mm]	weight [gr]	Total weight [Kg]
Central Cylinder	KK	320	1	63	61	2	200	0.2
Inside Cylinder	EAK	320	3	100	98	2	250	0.75
Up Horizontal Arm	AOB	41.4	3	20	18	2	111	0.333
Down Horizontal Arm	KOB	41.4	3	20	18	2	111	0.333
Up Inclined Arm	AKB	22	3	20	18	2	60	0.18
Down Inclined Arm	KKB	22	3	20	18	2	60	0.18
Diagonal Arm	ΔB	30.3	3	20	18	2	111	0.333
Wood screws		10	30	-	-	8	25	0.75
Metal angles		10 x 10	8	-	-	2	15	0.12
Metal hook		-	3	-	-	8	58	0.174
Metal screws		10	11	-	-	6	24	0.264
Metal washer		-	54	12	-	2	5	0.27
Metal nut		-	23	-	-	-	5	0.115
Screw plugs		10	30	-	-	8	7	0.21
Total [kg]								4.212


Construction of the model

- Video

Laboratory Equipment

- Video ect



Experimental Campaign 1/2




Experimental Campaign 2/2

- Video

Wave run up measurements 1/3




Wave run up measurements 2/3



Wave run up Statistics 3/3

T [sec]	min	max	mean	std
1.561	-0.29234	0.267019	0.00	0.192088
1.391	-0.77645	0.251969	0.00	0.363279
1.306	0.47696	0.861381	0.01	0.131719
1.208	-1.98671	-0.17319	-0.01	0.604489
1.103	-1.24299	-0.06533	-0.01	0.405085
1.032	-1.77852	1.08223	0.00	0.983586
0.9697	-0.45769	0.579504	0.00	0.359793
0.9143	-1.26083	1.24016	0.00	0.868691
0.8649	-2.01015	1.07065	0.00	1.037346
0.8205	-1.58267	0.356953	-0.01	0.695835
0.7805	-0.65551	0.738653	0.00	0.466151


Conclusions



Same wave elevation in any wind condition



Structure Motion response is small



TLP systems are more economical
in deep waters

Acknowledgments

This research has been partially financed by the General Secretariat for Research and Technology (GSRT) - Hellenic Foundation for Research and Innovation (HFRI), Research Projects for Postdoctoral Researchers, Program: FHMES: Floating Hybrid Mooring Wind Turbine Energy System, with Coordinator and Scientific Responsible Professor Thomas Mazarakos. This support is greatly appreciated.

Experimental Investigation of the Wave Run Up on a TLP Floating Wind Turbine

Marinos P. Charalambous

Email: marinoscharalambous93@gmail.com

